



■ PROWORKS® TOTAL GRIP LATEX GLOVES

Key Features

- Heavier duty than standard latex gloves
- Palm: 6.5 mil; Fingers: 7.5 mil
- Excellent comfort and fit
- Beaded cuff; microtextured fingers
- Double chlorinated for easy donning and increased solvent resistance

Standard

Meets ASTM D3578-05

Applications

Manufacturing/Automotive

- Paint booth
- Mechanical work and assembly
- Precision manufacturing
- Any mechanical or industrial applications where increased durability over a basic latex glove is desirable

Medical

- Patient exam
- Dental procedures
- Laboratory use
- Medical equipment manufacturing
- Pharmaceutical manufacturing

Additional Market Segments

Law Enforcement, Landscaping/Agriculture, Food Processing



Item #	Description	Color	Size	Glove Length	Glove Width	Glove Weight	Selling Unit
GL-L165FS	Powder Free	Natural	Small	240 mm	84 ± 3 mm	7.7 ± 0.4 g	100/bx - 10 bxs/cs
GL-L165FM	Powder Free	Natural	Medium	240 mm	94 ± 3 mm	8.2 ± 0.4 g	100/bx - 10 bxs/cs
GL-L165FL	Powder Free	Natural	Large	240 mm	105 ± 3 mm	8.7 ± 0.4 g	100/bx - 10 bxs/cs
GL-L165FX	Powder Free	Natural	X-Large	240 mm	113 ± 3 mm	9.2 ± 0.4 g	100/bx - 10 bxs/cs